

innoSCAN - 10mini

Features

- » High precision
- » Compact construction
- » Sealed housing
- » Competitive price
- » Performance improvement



TECHNICAL SPECIFICATIONS

Input Aperture	10 mm
Wavelength	355, 532, 1064, 10600 nm
Tracking error time	0.17 ms
Writing Speed ^{1 2}	> 640 cps
Positioning Speed ¹	> 7 m/s
Typical Deflection	± 0.35 rad
Resolution	16 bit
Repeatability (RMS)	< 20 µrad
Max. Gain drift ³	100 ppm/K
Max. Offset drift ³	50 µrad/K

¹ with F-theta-lens, f = 160 mm

² Single-stroke font , 1 mm height

Long-Term Drift (8h) ³	< 0,3 mrad
Zero Offset	< 6 µrad
Digital Interface	XY2-100 Protocol
Analog Interface	±5V
Ambient Temperature	+15 to +35 °C
Storage Temperature	-20 to +60 °C
Humidity	≤ 80% Non-condensing
Voltage / Current	15 V± DC / max. 3A
Weight	ca. 0.7 kg
Dimensions L x W x H	100 x 70.5 x 78.3 mm

³ Drift per axis

⁴ After warming-up

innoSCAN - 10mini

